W 44 T[®] Multi-Spray



Multifunctional oil with multiple effects

WEICON W 44 T[®] is a multifunctional product which combines corrosion protection, water repellency, lubrication, conservation and cleaning in a single product due to its special formula and outstanding capillary action. It loosens seized up screw connections, bolts, fittings and valves, and penetrates and dissolves rust. It repels humidity from electrical contacts, prevents leakage currents, and makes it easier to start wet motors. W 44 T[®] is also suitable for use as cutting oil for drilling and cutting processes. The oil eliminates squeaky and creaky noises on hinges, guides, bearings, and all types of joints and couplings. WEICON W 44 T[®] cleans soiled metal surfaces and leaves a long-lasting razorthin film, which does not smear or stick and does not attract dust. It protects and maintains all types of tools, machines, and electrical and mechanical precision devices.

Technische Daten		
Odour		vanilla
Colour		pale yellow, transparent
Specific properties		Multifunction oil with compound action
Silicone-free		yes
Kinematic viscosity (40 °C)	DIN 51 562	21 mm²/s
Kinematic viscosity (+100 °C)	DIN 51 562	4 mm²/s
Temperature resistance		-50 °C to +210 °C
Shelf life		24 mon.
Approvals / Guidelines		
ISSA Code		53.402.11

Technical Sprays Lubricating and Multifunctional Oils

Processing

Shake can before use. Apply W 44 T from a distance of approx. 5 cm and allow to take effect for approx. 30 seconds.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50 °C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

- 11251050 W 44 T[®] Multi-Spray, 50 ml, pale yellow, transparent
- 11251200 W 44 T[®] Multi-Spray, 200 ml, pale yellow, transparent
- 11251400 W 44 T[®] Multi-Spray, 400 ml, pale yellow, transparent
- 11251550 W 44 T[®] Multi-Spray, 500 ml, pale yellow, transparent

To the product detail



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarante the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es WEICON GmbH & Co. KG (Headquaters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Italia S.r.L. Italy phone +39 (0) 010 2924 871 info@weicon.it WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr